

**Starck 3 Wall Mounted Toilet # 222509..92 / 222509..92**

|&lt; 14 3/8 " &gt;|



Wall Mounted Toilet	Dimension	Weight	Order number
Flush water quantity: 1.2/0.8 gal, Washdown model, Flushing rim: Closed, Flush system: washdown model, Outlet horizontal, Concealed fixation, ADA: Yes, cUPC listed: Yes			
<b>Colors</b>			
00 White 20 HygieneGlaze (an antibacterial ceramic glaze that provides almost indefinite effectiveness)			
<b>Variant</b>			
White High Gloss, Flush water quantity: 1.6/0.8 gal, WaterSense: Yes		59.525 lb	222509..92
White High Gloss, HygieneGlaze, Flush water quantity: 1.6/0.8 gal, WaterSense: Yes		59.525 lb	222509..92
<b>Accessory for ceramics</b>			
Mounting Bracket Suitable for Bidet, Wall Mounted Toilet	Ø 1/2 "	0.617 lb	006500
<b>Spare parts</b>			
Noise reduction gasket	16 1/2 x 15 3/8 "	0.441 lb	005090
<b>Suitable products</b>			
Toilet Seat Slow close: No, Hinge material: Stainless Steel, 14 5/8 x 17 1/8 "	14 5/8 x 17 1/8 "		006381
Toilet Seat Slow close: Yes, Removable Seat, Hinge material: Stainless Steel, 14 5/8 x 17 "	14 5/8 x 17 "		006389
Actuator Plate A1 Plastic, Dual Flush, Trip lever type: Mechanical, Flush operation technology: Manual, Installation Type: surface mounted, Includes mounting frame, including mounting kit, Includes push rod, 8 1/2 x 3/8 "	8 1/2 x 3/8 "		WD5008
In-Wall Tank & Carrier Standard Includes HDPE toilet wall-mounted outlet bend DN 90/90, Powder-coated, Installation Type: In lightweight stand construction, Installation Type: Drywall, Max. projection toilet: 24 5/8 ", Adjustable height: 9 1/2 ", Trip lever type: Mechanical, Trip lever placement: Front, Adjustable flush volumes, Flush type: Dual Flush, Insulated tank, Self-supporting, Suitable for panelling with plasterboards, 23 1/4 x 3 1/2 "	23 1/4 x 3 1/2 "		WD1022

**Starck 3 Wall Mounted Toilet # 222509..92 / 222509..92**

**|< 14 3/8 " >|**

*All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.*